

Certificate of Compliance



Netstec Technology Corp. hereby declares that testing has been completed and reports have been generated for:

Applicant: Netstec Technology Corp

Address: No.2, Ln. 173, Sec. 2, Tailin Rd., Taishan Dist., New Taipei City, Taiwan

Brand: NETSTEC

Products: Surge Protector Device

Model: NTC-024 / NTC-048 / NTC-110 、LS-RJ45100M / LS-RJ451000M
LS-RJ11/M2 、NTC-300/15A 、LS-BNC 、DCP-24

That product has been assessed against the following applicable standards;

IEC61643-21 / EN61643-11

FCC Part 15 Class B

Therefore, Netstec Technology Corp. hereby acknowledges that the applicant may issue a certificate of compliance and apply the CE and FCC marking in accordance with European Union Rules / USA Rules

Zertificat Nr. R 50397907

Date of issued: Jan 12 .2018



Dipl.-Ing (FH) R. Keller

[Contents]

1. Client information	4
2. Laboratory information.....	5
3. Description of E.U.T.	6
3.1 Basic description.....	6
3.2 General description.....	6
3.3 Ambient Conditions	7
3.4 Test frequency.....	7
3.5 Test Voltage	7
3.6 Duty Cycle Correction Factor.....	7
4. Summary of test results	8
4.1 Standards & results.....	8
4.2 Uncertainty.....	8
5. Test results	9
5.1 Antenna Requirement	9
5.2 Maximum Peak Output Power	10
5.3 Peak Power Spectral Density	12
5.4 6 dB Bandwidth(DTS Channel Bandwidth).....	16
5.5 Spurious Emission, Band Edge, and Restricted bands	21
5.6 Conducted Emission	35
6. Test equipment used for test	37

Zertificat Nr. R 50397907



1. Client information

Applicant: Netstec Technology Corp
Address: No.2, Ln.173, Sec.2, Tailin Rd., Taishan Dist., New Taipei City, Taiwan
Telephone number: +886 2 23376277
Contact person: mit.hsu@netstec.com.tw

2. Products

Models: LS-RJ45 100M / LS-RJ45 1000M

3. Testing following requested

IEC61643-21 / EN61643-11
FCC Part 15 Class B

Zertificat Nr. R 50397907

3. Description of E.U.T.

3.1 Basic description

Applicant	Netstec Technology Corp
Address of Applicant	No.2,Ln.173, Sec.2,Tailin Rd.,Taishan Dist.,New Taipei , Taiwan
Manufacturer	Netstec Technology Corp
Address of Manufacturer	No.2,Ln.173, Sec.2,Tailin Rd.,Taishan Dist.,New Taipei , Taiwan
Type of equipment	Surge Protector Device
Basic Model	LS-RJ45 100M / LS-RJ45 1000M
Serial number	N/A

3.2 General description

Frequency Range	93.5 MHz ~ 927.5 MHz
Type of Modulation	RJ 45
The number of channels	1 Channel
Type of Antenna	External Antenna (Omni Antenna)
Antenna Gain	2.85 dBi
Transmit Power	23.49 dBm
Operation temperature	23 °C
Power supply	DC 48 V
Surge Testing version	15 KV
Bandwidth	10/100M,1000M
Test Version	10/700us , L-L / L-G
RF power setting in TEST	

Zertificat Nr. R 50397907



3.3 Ambient Conditions

	Temperature [°C]	Relative humidity [%]
Ambient Conditions	20	85


3.4 Test frequency

	900 MHz
Lowest frequency	923.3 MHz
Middle frequency	925.1 MHz
Highest frequency	927.5 MHz

3.5 Test Voltage

Mode	Voltage
Nominal Voltage	DC 48 V

3.6 Duty Cycle Correction Factor



Note) : The measurement was performed with continuous transmission (Duty cycle: $\geq 98\%$)

4. Summary of test results

4.1 Standards & results

FCC Rule Reference	Parameter	Report Section	Test Result
15.203, 15.247(b)(4)	Antenna Requirement	5.1	C
15.247(b)(3)	Maximum Peak Output Power	5.2	C
15.247(e)	Peak Power Spectral Density	5.3	C
15.247(a)(2)	6 dB Channel Bandwidth	5.4	C
-	Occupied Bandwidth	5.4	C
15.247(d),15.205(a),15.209(a)	Spurious Emission, Band Edge and Restricted bands	5.5	C
15.207(a)	Conducted Emissions	5.6	C
Note: C = complies, NC = Not complies, NT = Not tested, NA = Not Applicable			

4.2 Uncertainty

Measurement Item	Expanded Uncertainty $U = kU_c (k = 2)$	
Conducted RF power	1.44 dB	
Conducted Spurious Emissions	1.52 dB	
Radiated Spurious Emissions	30 MHz ~ 300 MHz:	+4.94 dB, -5.06 dB
		+4.93 dB, -5.05 dB
	300 MHz ~ 1 000 MHz:	+4.97 dB, -5.08 dB
		+4.84 dB, -4.96 dB
	1 GHz ~ 25 GHz:	+6.03 dB, -6.05 dB
Conducted Emissions	9 kHz ~ 150 kHz:	3.75 dB
	150 kHz ~ 30 MHz:	3.36 dB

Zertifikat Nr. R 50397907

5. Test results

5.1 Antenna Requirement

5.1.1 Regulation

According to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

And according to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

5.1.2 Result

-Complied

The transmitter has an antenna that uses a unique coupling to the intentional radiator.

Zertificat Nr. R 50397907

5.2 Maximum Peak Output Power

5.2.1 Regulation

According to §15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2 400-2 483.5 MHz, and 5 725-5 850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

According to §15.247(b)(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

5.2.2 Measurement Procedure

These test measurement settings are specified in section 9.0 of 558074 D01 DTS Meas Guidance.

5.2.2.1 PKPM1 Peak-reading power meter method

The maximum peak conducted output power may be measured using a broadband peak RF power meter.

The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

5.2.3 Test Result

- Complied

Channel	Frequency [MHz]	Result [dBm]	Limit [dBm]	Margin [dB]	Average power [dBm]
Lowest	923.3	23.09	30.00	6.91	22.25
Middle	925.1	23.49	30.00	6.51	22.57
Highest	927.5	23.19	30.00	6.81	22.28

NOTE:

1. We took the insertion loss of the cable loss into consideration within the measuring instrument.

Zertificat Nr. R 50397907



5.3 Peak Power Spectral Density

5.3.1 Regulation

According to §15.247(e), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

5.3.2 Measurement Procedure

These test measurement settings are specified in section 10.0 of 558074 D01 DTS Meas Guidance.

5.3.2.1 Method PKPSD (peak PSD)

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance, and is optional if the maximum conducted (average) output power was used to demonstrate compliance.

- 1) Set analyzer center frequency to DTS channel center frequency.
- 2) Set the span to 1.5 times the DTS bandwidth.
- 3) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- 4) Set the VBW $\geq 3 \times \text{RBW}$.
- 5) Detector = peak.
- 6) Sweep time = auto couple.
- 7) Trace mode = max hold.
- 8) Allow trace to fully stabilize.
- 9) Use the peak marker function to determine the maximum amplitude level within the RBW.
- 10) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.3.3 Test Result

- Complied

Channel	Frequency [MHz]	Result (RBW=3 kHz) [dB m/3 kHz]	Limit [dBm/3 kHz]	Margin [dB]
Lowest	923.3	3.11	8.00	4.89
Middle	925.1	3.28	8.00	4.72
Highest	927.5	2.92	8.00	5.08

NOTE:


1. We took the insertion loss of the cable loss into consideration within the measuring instrument.

Zertificat Nr. R 50397907


5.3.4 Test Plot

Figure 1. Plot of the Power Density

Lowest Channel (923.3 MHz)




Middle Channel (925.1 MHz)



Zertificat Nr. R 50397907

Highest Channel (927.5 MHz)



Zertificat Nr. R 50397907

5.4 6 dB Bandwidth(DTS Channel Bandwidth)

5.4.1 Regulation

According to §15.247(a)(2) Systems using digital modulation techniques may operate in the 902–928 MHz, 2 400–2 483.5 MHz, and 5 725–5 850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

5.4.2 Measurement Procedure

These test measurement settings are specified in section 8.0 of 558074 D01 DTS Meas Guidance.

5.4.2.1 DTS Channel Bandwidth-Option 1

- 1) Set RBW = 100 kHz.
- 2) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- 3) Detector = Peak.
- 4) Trace mode = max hold.
- 5) Sweep = auto couple.
- 6) Allow the trace to stabilize.
- 7) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.4.3 Test Result

- Complied

Channel	Frequency [MHz]	6 dB Bandwidth [MHz]	Min. Limit [MHz]	Occupied Bandwidth (99 % BW) [MHz]
Lowest	923.3	0.58	0.50	0.49
Middle	925.1	0.58	0.50	0.49
Highest	927.5	0.57	0.50	0.49

NOTE:


1. We took the insertion loss of the cable loss into consideration within the measuring instrument.

5.4.4 Test Plot


Figure 2. Plot of the 6 dB Bandwidth & Occupied Bandwidth

- 6 dB Bandwidth

Lowest Channel (923.3 MHz)




Middle Channel (925.1 MHz)



Zertificat Nr. R 50397907

Highest Channel (927.5 MHz)



- Occupied Bandwidth

Lowest Channel (923.3 MHz)



Middle Channel (925.1 MHz)



Highest Channel (927.5 MHz)



Zertificat Nr. R 50397907

5.5 Spurious Emission, Band Edge, and Restricted bands

5.5.1 Regulation

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

According to §15.209(a), Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field strength ($\mu V/m$)	Measurement distance (m)
0.009 - 0.490	2 400/F(kHz)	300
0.490 - 1.705	24 000/F(kHz)	30
1.705 - 30	30	30
30 - 88	100**	3
88 - 216	150**	3
216 - 960	200**	3
Above 960	500	3

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54–72 MHz, 76–88 MHz, 174–216 MHz or 470–806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.

According to § 15.205(a) and (b), only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.009 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
0.495 - 0.505	16.694 75 - 16.695 25	608 - 614	5.35 - 5.46
2.173 5 - 2.190 5	16.804 25 - 16.804 75	960 - 1 240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1 300 - 1 427	8.025 - 8.5
4.177 25 - 4.177 75	37.5 - 38.25	1 435 - 1 626.5	9.0 - 9.2
4.207 25 - 4.207 75	73 - 74.6	1 645.5 - 1 646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1 660 - 1 710	10.6 - 12.7
6.267 75 - 6.268 25	108 - 121.94	1 718.8 - 1 722.2	13.25 - 13.4
6.311 75 - 6.312 25	123 - 138	2 200 - 2 300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2 310 - 2 390	15.35 - 16.2
8.362 - 8.366	156.524 75 - 156.525 25	2 483.5 - 2 500	17.7 - 21.4
8.376 25 - 8.386 75	156.7 - 156.9	2 690 - 2 900	22.01 - 23.12
8.414 25 - 8.414 75	162.012 5 - 167.17	3 260 - 3 267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3 332 - 3 339	31.2 - 31.8
12.519 75 - 12.520 25	240 - 285	3 345.8 - 3 358	36.43 - 36.5
12.576 75 - 12.577 25	322 - 335.4	3 600 - 4 400	Above 38.6
13.36 - 13.41			

The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in §15.209. At frequencies equal to or less than 1 000 MHz, compliance with the limits in §15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1 000 MHz, compliance with the emission limits in §15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in §15.35 apply to these measurements.

Zertificat Nr. R 50397907



5.5.2 Measurement Procedure

5.5.2.1 Band-edge Compliance of RF Conducted Emissions

5.5.2.1.1 Reference Level Measurement

Establish a reference level by using the following procedure:

- 1) Set instrument center frequency to DTS channel center frequency.
- 2) Set the span to ≥ 1.5 times the DTS bandwidth.
- 3) Set the RBW = 100 kHz.
- 4) Set the VBW $\geq 3 \times$ RBW.
- 5) Detector = peak.
- 6) Sweep time = auto couple.
- 7) Trace mode = max hold.
- 8) Allow trace to fully stabilize.
- 9) Use the peak marker function to determine the maximum PSD level.

5.5.2.1.2 Emissions Level Measurement

- 1) Set the center frequency and span to encompass frequency range to be measured.
- 2) Set the RBW = 100 kHz.
- 3) Set the VBW $\geq 3 \times$ RBW.
- 4) Detector = peak.
- 5) Ensure that the number of measurement points \geq span/RBW
- 6) Sweep time = auto couple.
- 7) Trace mode = max hold.
- 8) Allow trace to fully stabilize.
- 9) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.

5.5.2.2 Conducted Spurious Emissions

Set the spectrum analyzer as follows:

- 1) Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic.

Typically, several plots are required to cover this entire span.

- 2) RBW = 100 kHz
- 3) VBW \geq RBW
- 4) Sweep = auto
- 5) Detector function = peak
- 6) Trace = max hold
- 7) Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded.
- 8) Each frequency found during preliminary measurements was re-examined and investigated.
The test-receiver system was set up to average, peak, and quasi-peak detector function with specified bandwidth.

5.5.2.3 Radiated Spurious Emissions

- 1) The preliminary and final radiated measurements were performed to determine the frequency producing the maximum emissions in at a 10m anechoic chamber. The EUT was tested at a distance 3 meters.
- 2) The EUT was placed on the top of the 0.8-meter height, 1 × 1.5 meter non-metallic table. To find the maximum emission levels, the height of a measuring antenna was changed and the turntable was rotated 360°.
- 3) The antenna polarization was also changed from vertical to horizontal. The spectrum was scanned from 9 kHz to 30 MHz using the loop antenna, and from 30 to 1 000 MHz using the TRILOG broadband antenna, and from 1 000 MHz to 26 500 MHz using the horn antenna.
- 4) Each frequency found during preliminary measurements was re-examined and investigated. The test-receiver system was set up to average, peak, and quasi-peak detector function with specified bandwidth.
- 5) The 0.8m height is for below 1 G testing, and 1.5m is for above 1G testing.

Note

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1 GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection and frequency above 1 GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Average detection (AV) at frequency above 1 GHz. (Detector = RMS, Averaging type = power)
In case of duty cycle less than 98%, a duty cycle correction factor has to be added to the measurement result.

5.5.3 Test Result

- Complied

1. Band edge & Conducted Spurious Emissions was shown in figure 3 & 4.
Note: We took the insertion loss of the cable into consideration within the measuring instrument.
 2. Measured value of the Field strength of spurious Emissions (Radiated)
 3. It tested x,y and z – 3 axis each, mentioned only worst case data at this report.
- ※ Noise was not measured. (Margin was more than 20 dB)

- Below 1 GHz data (worst-case: Middle channel_925.1 MHz)

Middle channe (925.1 MHz)

Frequency [MHz]	Receiver Bandwidth [kHz]	Pol. [V/H]	Reading [dB(μV)]	Cable Loss [dB]	Amp Gain [dB]	Antenna Factor [dB]	Factor [dB]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]
Quasi-Peak DATA. Emissions below 30 MHz										
0.56	9	H	47.00	0.03	-32.73	19.6	-13.10	33.90	72.70	38.80
9.93	9	V	40.10	0.77	-32.67	19.7	-12.20	27.90	69.50	41.60

NOTE 1. Factor = Cable loss + Amplifier gain + Antenna factor

NOTE 2. Although these tests were performed other than open field test site, adequate comparison measurements were confirmed against 30 m open field test site.

Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

Zertificat Nr. R 50397907

Lowest channel (923.3 MHz)

Frequency [MHz]	Receiver Bandwidth [kHz]	Pol. [V/H]	Reading [dB(μV)]	Cable Loss [dB]	Amp Gain [dB]	Antenna Factor [dB]	Factor [dB]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]
Quasi-Peak DATA. Emissions below 1 GHz										
31.94	120	V	45.80	1.12	-41.03	23.91	-16.00	29.80	40.00	10.20
76.92	120	H	44.80	1.84	-32.36	12.92	-17.60	27.20	40.00	12.80
127.97	120	V	45.30	2.44	-35.24	17.90	-14.90	30.40	43.50	13.10
159.98	120	V	51.90	2.77	-31.97	16.10	-13.10	35.70	38.80	3.10
191.99	120	V	46.30	3.05	-34.01	15.26	-15.70	30.60	43.50	12.90
224.00	120	V	46.80	3.31	-35.10	16.69	-15.10	31.70	46.00	14.30

Middle channel (925.1 MHz)

Frequency [MHz]	Receiver Bandwidth [kHz]	Pol. [V/H]	Reading [dB(μV)]	Cable Loss [dB]	Amp Gain [dB]	Antenna Factor [dB]	Factor [dB]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]
Quasi-Peak DATA. Emissions below 1 GHz										
95.96	120	V	45.10	2.09	-37.06	15.87	-19.10	26.00	43.50	17.50
159.98	120	V	53.70	2.99	-43.49	27.40	-13.10	40.60	43.50	2.90
191.99	120	V	44.60	3.44	-52.30	33.16	-15.70	28.90	43.50	14.60
224.00	120	V	50.00	3.31	-35.10	16.69	-15.10	34.90	46.00	11.10
320.03	120	V	43.80	4.06	-37.02	22.26	-10.70	33.10	46.00	12.90

Highest channel (927.5 MHz)

Frequency [MHz]	Receiver Bandwidth [kHz]	Pol. [V/H]	Reading [dB(μV)]	Cable Loss [dB]	Amp Gain [dB]	Antenna Factor [dB]	Factor [dB]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]
Quasi-Peak DATA. Emissions below 1 GHz										
95.96	120	V	43.60	2.09	-37.06	15.87	-19.10	24.50	43.50	19.00
159.98	120	V	54.40	2.77	-31.97	16.10	-13.10	41.30	43.50	2.20
224.00	120	V	45.20	3.31	-35.10	16.69	-15.10	30.10	46.00	15.90
249.95	120	V	47.10	3.51	-35.21	18.20	-13.50	33.60	46.00	12.40
256.01	120	V	45.70	3.55	-35.07	18.32	-13.20	32.50	46.00	13.50

NOTE 1. Factor = Cable loss + Amplifier gain + Antenna factor

NOTE 2. Although these tests were performed other than open field test site, adequate comparison measurements were confirmed against 30 m open field test site.

Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

Zertifikat Nr. R 50397907

- Above 1 GHz data

Lowest channel (923.3 MHz)

Frequency [MHz]	Receiver Bandwidth [kHz]	Pol. [V/H]	Reading [dB(μV)]	Cable Loss [dB]	Amp Gain [dB]	Antenna Factor [dB]	DCCF [dB]	Factor [dB]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]
Peak DATA. Emissions above 1 GHz											
1 846.56 ²⁾	1 000	H	49.94	3.28	-32.83	27.19	-	-2.36	47.58	74.00	26.42
2 261.13 ¹⁾	1 000	H	43.98	3.61	-33.00	28.30	-	-1.09	42.88	74.00	31.12
2 769.91 ^{1,2)}	1 000	H	44.05	3.97	-34.49	29.26	-	-1.26	42.80	74.00	31.20
3 693.25 ^{1,2)}	1 000	V	49.57	4.59	-33.57	31.57	-	2.59	52.16	74.00	21.84
4 616.31 ^{1,2)}	1 000	H	44.34	5.21	-33.07	32.71	-	4.85	49.19	74.00	24.81
5 539.09 ^{1,2)}	1 000	H	43.66	5.81	-32.08	33.71	-	7.44	51.09	74.00	22.91
Average DATA. Emissions above 1 GHz											
2 261.13 ¹⁾	1 000	H	40.91	3.61	-33.00	28.30	-	-1.09	39.82	54.00	14.18
2 769.91 ^{1,2)}	1 000	H	40.98	3.97	-34.49	29.26	-	-1.26	39.72	54.00	14.28
3 693.25 ^{1,2)}	1 000	V	45.09	4.59	-33.57	31.57	-	2.59	47.68	54.00	6.32
4 616.31 ^{1,2)}	1 000	H	38.35	5.21	-33.07	32.71	-	4.85	43.20	54.00	10.80
5 539.09 ^{1,2)}	1 000	H	39.42	5.81	-32.08	33.71	-	7.44	46.86	54.00	7.14

Factor = Cable loss + Amplifier gain + Antenna factor

¹⁾ Restricted band

²⁾ Harmonic

Zertifikat Nr. R 50397907

Middle channel (925.1 MHz)

Frequency [MHz]	Receiver Bandwidth [kHz]	Pol. [V/H]	Reading [dB(μV)]	Cable Loss [dB]	Amp Gain [dB]	Antenna Factor [dB]	DCCF [dB]	Factor [dB]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]
Peak DATA. Emissions above 1 GHz											
1 729.01	1 000	H	49.09	3.17	-32.89	26.72	-	-3.00	46.09	74.00	27.91
1 849.94 ²⁾	1 000	H	49.06	3.28	-33.45	27.20	-	-2.97	46.09	74.00	27.91
2 435.50	1 000	H	48.26	3.74	-34.72	28.63	-	-2.35	45.91	74.00	28.09
3 700.28 ¹⁾	1 000	V	46.73	4.59	-36.98	31.59	-	-0.80	45.93	74.00	28.07
4 625.31 ^{1,2)}	1 000	V	49.57	5.21	-35.33	32.71	-	2.59	52.16	74.00	21.84
5 096.97 ¹⁾	1 000	H	39.68	5.53	-28.52	33.05	-	10.06	49.74	74.00	24.26
Average DATA. Emissions above 1 GHz											
3 700.28 ¹⁾	1 000	V	45.56	4.59	-36.98	31.59	-	-0.80	44.76	54.00	9.24
4 625.31 ¹⁾	1 000	V	39.54	5.21	-35.33	32.71	-	2.59	42.13	54.00	11.87
5 096.97 ¹⁾	1 000	H	28.40	5.53	-28.52	33.05	-	10.06	38.46	54.00	15.54

Factor = Cable loss + Amplifier gain + Antenna factor

¹⁾ Restricted band

²⁾ Harmonic

Highest channel (927.5 MHz)

Frequency [MHz]	Receiver Bandwidth [kHz]	Pol. [V/H]	Reading [dB(μV)]	Cable Loss [dB]	Amp Gain [dB]	Antenna Factor [dB]	DCCF [dB]	Factor [dB]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]
Peak DATA. Emissions above 1 GHz											
1 728.97	1 000	V	46.97	3.17	-32.86	26.72	-	-2.97	44.00	74.00	30.00
1 855.28 ²⁾	1 000	H	47.34	3.29	-32.84	27.22	-	-2.33	45.01	74.00	28.99
2 260.84 ¹⁾	1 000	H	43.63	3.61	-33.01	28.30	-	-1.10	42.53	74.00	31.47
2 434.66	1 000	H	46.66	3.74	-33.17	28.63	-	-0.80	45.86	74.00	28.14
3 710.13 ^{1,2)}	1 000	V	50.07	4.60	-33.58	31.62	-	2.64	52.72	74.00	21.28
4 637.69 ^{1,2)}	1 000	V	43.98	5.22	-33.10	32.72	-	4.84	48.82	74.00	25.18
Average DATA. Emissions above 1 GHz											
2 260.84 ¹⁾	1 000	H	41.28	3.61	-33.01	28.30	-	-1.10	40.18	54.00	13.82
3 710.13 ^{1,2)}	1 000	V	46.02	4.60	-33.58	31.62	-	2.64	48.66	54.00	5.34
4 637.69 ^{1,2)}	1 000	V	38.53	5.22	-33.10	32.72	-	4.84	43.37	54.00	10.63

Factor = Cable loss + Amplifier gain + Antenna factor

¹⁾ Restricted band

²⁾ Harmonic


Zertifikat Nr. R 50397907

5.7.4 Test Plot


Figure 3. Plot of the Band-edge & Conducted Spurious Emissions

Lowest Channel (923.3 MHz)

Reference




Band-edge



- Result of 923.3 MHz


Zertificat Nr. R 50397907

Conducted Spurious Emissions




Middle Channel (925.1 MHz)

Reference




Zertificat Nr. R 50397907

Conducted Spurious Emissions




Highest Channel (927.5 MHz)

Reference




Zertificat Nr. R 50397907

Band-edge



- Result of 927.5 MHz

Conducted Spurious Emissions



Zertificat Nr. R 50397907

5.6 Conducted Emission

5.6.1 Regulation

According to §15.207(a), for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56 *	56 to 46 *
0.5 – 5	56	46
5 – 30	60	50

* Decreases with the logarithm of the frequency.

According to §15.107(a), for unintentional device, except for Class A digital devices, line conducted emission limits are the same as the above table.

5.6.2 Measurement Procedure


- 1) The EUT was placed on a wooden table of size, 1 m by 1.5 m, raised 80 cm in which is located 40 cm away from the vertical wall and 1.5m away from the side wall of the shielded room.
- 2) Each current-carrying conductor of the EUT power cord was individually connected through a 50 Ω /50 μ H LISN, which is an input transducer to a Spectrum Analyzer or an EMI/Field Intensity Meter, to the input power source.
- 3) Exploratory measurements were made to identify the frequency of the emission that had the highest amplitude relative to the limit by operating the EUT in a range of typical modes of operation, cable position, and with a typical system equipment configuration and arrangement. Based on the exploratory tests of the EUT, the one EUT cable configuration and arrangement and mode of operation that had produced the emission with the highest amplitude relative to the limit was selected for the final measurement.
- 4) The final test on all current-carrying conductors of all of the power cords to the equipment that comprises the EUT (but not the cords associated with other non-EUT equipment is the system) was then performed over the frequency range of 0.15 MHz to 30 MHz.
- 5) The measurements were made with the detector set to PEAK amplitude within a bandwidth of 10 kHz or to QUASI-PEAK and AVERAGE within a bandwidth of 9 kHz. The EUT was in transmitting mode during the measurements.

5.6.3 Test Result

- Complied

Figure 6. plot of Conducted Emission

- Conducted worst-case data: Middle channel (925.1 MHz)



Final Result

--- N Phase ---										
No.	Frequency	Reading QP	Reading CAV	c. f	Result QP	Result CAV	Limit QP	Limit AV	Margin QP	Margin CAV
	[MHz]	[dB(uV)]	[dB(uV)]	[dB]	[dB(uV)]	[dB(uV)]	[dB(uV)]	[dB(uV)]	[dB]	[dB]
1	0.15572	34.2	8.3	10.1	44.3	18.4	65.7	55.7	21.4	37.3
2	0.17444	32.5	7.7	10.4	42.9	18.1	64.7	54.7	21.8	36.6
3	0.25229	49.0	40.4	10.0	59.0	50.4	61.7	51.7	2.7	1.3
4	0.28047	33.4	5.5	10.0	43.4	15.5	60.8	50.8	17.4	35.3
5	0.49745	32.3	27.3	10.1	42.4	37.4	56.0	46.0	13.6	8.6
6	16.22847	33.2	33.1	10.3	43.5	43.4	60.0	50.0	16.5	6.6
--- L1 Phase ---										
No.	Frequency	Reading QP	Reading CAV	c. f	Result QP	Result CAV	Limit QP	Limit AV	Margin QP	Margin CAV
	[MHz]	[dB(uV)]	[dB(uV)]	[dB]	[dB(uV)]	[dB(uV)]	[dB(uV)]	[dB(uV)]	[dB]	[dB]
1	0.2349	37.6	14.7	10.0	47.6	24.7	62.3	52.3	14.7	27.6
2	0.26755	36.0	11.6	9.9	45.9	21.5	61.2	51.2	15.3	29.7
3	0.3765	38.6	30.1	10.1	48.7	40.2	58.4	48.4	9.7	8.2
4	0.6287	26.2	22.2	10.1	36.3	32.3	56.0	46.0	19.7	13.7
5	1.23379	23.4	18.5	10.1	33.5	28.6	56.0	46.0	22.5	17.4
6	1.4869	21.8	18.3	10.0	31.8	28.3	56.0	46.0	24.2	17.7

Zertificat Nr. R 50397907

6. Test equipment used for test

	Equipment Name	Manufacturer	Model No.	Serial No.	Next Cal. Date
■	Spectrum Analyzer	R&S	FSV40	100988	19.01.05
■	EMI TEST RECEIVER	R&S	ESCI 3	100710	18.08.24
■	EMI TEST RECEIVER	R&S	ESCI7	100732	18.08.24
■	Wideband Power Sensor	R&S	NRP-Z81	102398	19.01.31
■	AC/DC Power Supply	KIKUSUI	PCR2000W	GB001619	18.09.27
■	Attenuator	R&S	DNF Dämpfungsglied 10 dB in N-50 Ohm	31210	18.05.15
■	Signal Generator	R&S	SMR40	100007	18.05.15
■	Vector Signal Generator	R&S	SMBV100A	257566	19.01.05
■	Horn Antenna	ETS.lindgren	3115	62589	18.11.21
■	Loop Antenna	R&S	HFH2-Z2	100355	20.01.31
■	Bilog Antenna	SCHWARZBECK	VULB9168	440	18.08.05
■	Attenuator	Agilent	8491A	MY52461848	18.08.24
■	AMPLIFIER	SONOMA	310N	186280	18.04.06
■	AMPLIFIER	SONOMA	310N	344922	18.08.25
■	Broadband PreAmplifier	SCHWARZBECK	BBV9718	216	18.08.01
■	High Pass Filter	Wainwright Instruments GmbH	WHK10-1290-1500-10000-60SS	1	18.08.06
■	Turn Table	Innco Systems	DT2000	79	-
■	Antenna Mast	Innco Systems	MA4640-XP-ET	-	-
■	Turn Table	Innco Systems	DT2000	79	-
■	Antenna Mast	Innco Systems	MA4000-EP	303	-
■	TWO-LINE V-NETWORK	R&S	ENV216	101352	18.08.25
■	Cable Assembly	RadiAll	2301761768000PJ	-	-
■	Cable Assembly	HUER+SUHNER	SUCOFLEX 104	MY4342/4	-
■	Cable Assembly	RadiAll	2301762000PJ	1724.66	-
■	Cable Assembly	Gigalane	RF-400	-	-

Zertificat Nr. R 50397907